

LOGO! DM16 230R, EXP. MODULE, PU/I/O: 230V/230V/RELAIS, 4TE, 8 DI/8 DO



Installation type/mounting

Mounting on DIN rail 25 mm, 4 module spaces wide

Supply voltage

Rated value (DC)

- 115 V DC Yes
- 230 V DC Yes

permissible range, lower limit (DC) 100 V

permissible range, upper limit (DC) 253 V

Rated value (AC)

- 115 V AC Yes
- 230 V AC Yes

Line frequency

- permissible range, lower limit 47 Hz
- permissible range, upper limit 63 Hz

Digital inputs

Number of digital inputs 8

Input voltage

- Type of input voltage AC/DC

<ul style="list-style-type: none"> • for signal "0" • for signal "1" 	<p>< 40 V AC, < 30 V DC</p> <p>> 79 V AC, > 79 V DC</p>
Input current	
<ul style="list-style-type: none"> • for signal "0", max. (permissible quiescent current) • for signal "1", typ. 	<p>0.05 mA</p> <p>0.12 mA</p>
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	50 ms
— at "1" to "0", max.	125 ms

Digital outputs	
Number of digital outputs	8; Relays
Short-circuit protection	No
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • on lamp load, max. 	1 000 W; 500 W at 115V AC
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value 	5 A
Parallel switching of two outputs	
<ul style="list-style-type: none"> • for uprating 	No
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. • with inductive load, max. • mechanical, max. 	<p>2 Hz</p> <p>0.5 Hz</p> <p>10 Hz</p>
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	5 A

EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> • Limit class B, for use in residential areas 	Yes

Degree and class of protection	
Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> • IP20 	Yes

Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes

Marine approval	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Dimensions	
Width	72 mm; 4 WU
Height	90 mm
Depth	53 mm
last modified:	05/23/2017