



\*\*\*Spare part\*\*\* SIMATIC S7-1200, Digital I/O SM 1223, 8 DI/8 DO, 8 DI 24 V DC, Sink/Source, 8 DO, relay 2 A

General information		
Product type designation	SM 1223, DI 8x24 V DC, DQ 8x relay	
Supply voltage		
Rated value (DC)	24 V	
permissible range, lower limit (DC)	20.4 V	
permissible range, upper limit (DC)	28.8 V	
Input current		
from backplane bus 5 V DC, max.	145 mA	
Digital inputs		
<ul style="list-style-type: none"> <li>from load voltage L+ (without load), max.</li> </ul>	4 mA/input 11 mA/relay	
output voltage / header		
supply voltage of the transmitters / header	<ul style="list-style-type: none"> <li>product function / supply voltage for transmitters</li> </ul>	Yes
Power loss		
Power loss, typ.	5.5 W	
Digital inputs		
Number of digital inputs	8	
<ul style="list-style-type: none"> <li>in groups of</li> </ul>	2	
Input characteristic curve in accordance with IEC 61131, type 1	Yes	
Number of simultaneously controllable inputs		
all mounting positions		
— up to 40 °C, max.	8	
horizontal installation		
— up to 40 °C, max.	8	
— up to 50 °C, max.	8	
vertical installation		
— up to 40 °C, max.	8	
Input voltage		
<ul style="list-style-type: none"> <li>Type of input voltage</li> <li>Rated value (DC)</li> <li>for signal "0"</li> <li>for signal "1"</li> </ul>	DC 24 V 5 V DC at 1 mA 15 V DC at 2.5 mA	
Input current		
<ul style="list-style-type: none"> <li>for signal "0", max. (permissible quiescent current)</li> <li>for signal "1", min.</li> <li>for signal "1", typ.</li> </ul>	1 mA 2.5 mA 4 mA	
Input delay (for rated value of input voltage)		
for standard inputs		

— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
for interrupt inputs	
— parameterizable	Yes
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	300 m
<b>Digital outputs</b>	
Number of digital outputs	8
• in groups of	2
Short-circuit protection	No; to be provided externally
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	2 A
• on lamp load, max.	30 W with DC, 200 W with AC
<b>Output voltage</b>	
• Rated value (DC)	5 to 30 V AC
• Rated value (AC)	5 V AC to 250 V AC
<b>Output current</b>	
• for signal "1" permissible range, max.	2 A
<b>Output delay with resistive load</b>	
• "0" to "1", max.	10 ms
• "1" to "0", max.	10 ms
<b>Total current of the outputs (per group)</b>	
horizontal installation	
— up to 50 °C, max.	10 A; Current per mass
<b>Relay outputs</b>	
• Number of relay outputs	8
• Rated supply voltage of relay coil L+ (DC)	24 V
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
<b>Switching capacity of contacts</b>	
— with inductive load, max.	2 A
— on lamp load, max.	30 W with DC, 200 W with AC
— with resistive load, max.	2 A
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Interrupts/diagnostics/status information</b>	
Alarms	Yes
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostics indication LED</b>	
• for status of the inputs	Yes
• for status of the outputs	Yes
• for maintenance	Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• between the channels, in groups of	2
<b>Potential separation digital outputs</b>	
• between the channels	Relays
• between the channels, in groups of	2
• between the channels and backplane bus	1 500 V AC for 1 minute
<b>Permissible potential difference</b>	
between different circuits	750 V AC for 1 minute
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
FM approval	Yes

RCM (formerly C-TICK)	Yes
<b>Ambient conditions</b>	
Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
• horizontal installation, min.	0 °C
• horizontal installation, max.	55 °C
• vertical installation, min.	0 °C
• vertical installation, max.	45 °C
• permissible temperature change	5°C to 55°C, 3°C / minute
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
Relative humidity	
• Operation at 25 °C without condensation, max.	95 %
<b>connection method / header</b>	
required front connector	Yes
<b>Mechanics/material</b>	
Enclosure material (front)	
• Plastic	Yes
<b>Dimensions</b>	
Width	45 mm
Height	100 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	230 g
<b>last modified:</b>	4/1/2022 