

Industrial control transformer, Type TF, 1 phase, 500VA, 240x480V primary, 120V secondary, 50/60Hz

9070TF500D1

Product availability: Stock - Normally stocked in distribution

Price\*: 573.00 USD

#### Main

mani			
<b>Product or Component Type</b>	Industrial Control Transformer		
Power Rating	500 VA		
Primary Voltage	240 x 480 V 220 x 440 V 230 x 460 V		
Secondary Voltage	115 V 110 V 120 V		
Туре	TF		

### Complementary

Number of Phases	1 phase			
	500 VA UL			
	500 VA CSA			
	500 VA NOM			
	300 VA NOW			
	300 VA			
Primary to Secondary Voltage	220 x 440 V 110 V			
,	230 x 460 V 115 V			
	240 x 480 V 120 V			
Fuse type	0.41 x 1.50 in CC top			
Temperature rise	115 °C			
Electrical Connection	Screw clamp terminals			
Height	5.13 in (130.30 mm)			
Width	4.5 in (114.30 mm)			
Depth	5.49 in (139.45 mm)			
Material	Copper winding			
<u> </u>	F000			
Fingersafe Cover Compatibility	FSC2			

#### **Environment**

Product Certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239	
Enclosure Type	Not rated (open device)	
Insulation temperature	356 °F (180 °C)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

### Ordering and shipping details

Category	16203-9070 TF (NOT T) 250-1000VA			
Discount Schedule	CP8			
GTIN	785901904892			
Nbr. of units in pkg.	1			
Package weight(Lbs)	12.70 lb(US) (5.761 kg)			
Returnability	Yes			
Country of origin	MX			

## **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	7.60 in (19.304 cm)	
Package 1 width	6.70 in (17.018 cm)	
Package 1 Length	6.20 in (15.748 cm)	

## Offer Sustainability


Sustainable offer status	Green Premium product  WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
California proposition 65			
REACh Regulation	REACh Declaration		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		
<b>Environmental Disclosure</b>	Product Environmental Profile		
PVC free	Yes		

## **Contractual warranty**

Warranty 18 months

**Dimensions Drawings** 

### **Approximate Dimensions**



# **Product data sheet**

# 9070TF500D1

Connections and Schema

### **Connections and Wiring Diagrams**

### **Voltage and Connection Options**

Voltage Code	Voltages		Connections	
	Primary	Secondary	Primary	Secondary
D1	220 x 440 230 x 460 240 x 480	110 115 120	220/230/240 V: Connect to H1 and H4 Jumper H1 and H3 Jumper H2 with H4 440/460/480 V: Connect to H1 and H4 Jumper H2 with H3	Connect to X1 and X2

