



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Transformers](#) > [Dry Type, Encapsulated, Enclosed](#)

Transformers, Dry Type, Encapsulated, Enclosed

Product #: 9T21B9103

Short Description: ENCLOSED MEDIUM POWER TRANSFORMERS

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Single-Phase:
Phase	1
PriVoltage	240x480
SecVoltage	120/240
KVA	15.0 KVA
Coil Material	AL
TempRise	115 °C
ElecShield	N
SubType	Standard
Frequency	60 Hz
UL	Yes
Impedance	0.0 %
FrameSize	19500
cUL	Yes
CE	No
Width	12.5 in
Depth	12.5 in
Height	17.1 in
TempClass	180 °C
AmbTemp	40 °C
InsulSys	IS-12
GSA Compliance	Yes
GO Schedule	90C
List Price	\$1943



[View Larger](#)

Publications/Resources

[9T21B9103](#)

Additional Resources for Single-Phase: .050kVA-3kVA and 5kVA-25kVA

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional Buy Log :8-52](#)

[Control Log : 15-10](#)

These GE transformers feature encapsulated core and coils in a NEMA 3R non-ventilated weatherproof enclosure

- UL Listed
- C-UL Listed
- Knockouts provided on back and bottom
- High grade silicon steel core
- Mounting holes on side for easy access
- Wiring compartment includes ground stud

