

## Eaton Series C complete molded case circuit breaker

**EHD1070L**

**UPC:**786679157008

### **Dimensions:**

- **Height:** 6 IN
- **Length:** 3.38 IN
- **Width:** 1.38 IN

**Weight:**1.65 LB

**Warranties:** No Data

### **Specifications:**

- **Amperage Rating:** 70A
- **Interrupt Rating:** 18 kAIC at 240 Vac, 14 kAIC at 480 Vac
- **Number Of Poles:** Single-pole
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** EHD
- **Circuit Breaker Frame Type:** Complete breaker
- **Series:** Series C
- **Terminals:** Line and load
- **Frame:** F-frame
- **Frequency Rating:** 50/60 Hz

### **Supporting documents:**

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Motor protection circuit breakers product aid](#)
- [MOEM MCCB Product Selection Guide](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)

- StrandAble terminals product aid
- Power metering and monitoring with Modbus RTU product aid
- Plug-in adapters for molded case circuit breakers product aid
- Multi-wire lugs product aid
- Molded case circuit breakers
- Eatons Volume 4-Circuit Protection
- EHD1 AutoCAD 2D Footprint (mm)
- EHD1 3D Inventor
- Time Current Curves for Series C® F-Frame Circuit Breakers
- EHD1 2D PDF
- EHD1 3D Model Xchange
- Installation Instructions for EHD, EDB, EDS, ED, EDH, EDC, FDB, FD, HFD, FDC, HFDDC Circuit Breakers and Molded Case Switches
- Breaker service centers
- Counterfeit and Gray Market Awareness Guide
- Series C J-Frame molded case circuit breakers time current curves
- MOEM MCCB product selection guide
- Series C G-Frame molded case circuit breakers time current curves
- Series C F-Frame molded case circuit breakers
- Eaton Specification Sheet - EHD1070L

**Certifications:**

- UL Listed

**Product compliance:** No Data