

Product data sheet

Specifications



busbar Easypact - 400 A - 8 ways

EZB400W08

! Discontinued on: 07 December 2020

EZB400W08 has not been replaced. Please contact your customer care center for more information.

! Discontinued

Main

Range of product	EasyPact
Range	EasyPact
Device short name	busbar
Product or component type	Busbar
Device application	Connection
Range compatibility	EasyPact EZB circuit breaker
[In] rated current	400 A
Number of ways	8 ways

Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ue] rated operational voltage	550 V AC 50/60 Hz
Number of devices	12 (2P) 24 (1P) 8 (3P)
Busbar extension	2 or 4 ways
[Icw] rated short-time withstand current	40 kA for 1 s
Height	440 mm
Width	416 mm
Depth	107 mm

Environment

Standards	IEC 60439
-----------	-----------

Packing Units

Package 1 Weight	8.375 kg
Package 1 Height	1.400 dm
Package 1 width	4.500 dm
Package 1 Length	5.000 dm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------
