TeSys LC1D.K capacitor duty contactor - 3P - 25 kVAR - 415 V - 110 V AC coil

LC1DMK11F7

EAN Code: 3389110059137

Main

Range	TeSys
Product name	TeSys LC1D.K
Product or component type	Capacitor duty contactor
Device short name	LC1DMK
Contactor application	Power factor correction
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: <= 690 V AC 50/60 Hz
Reactive power rating	15 kvar at 220240 V AC 50/60 Hz 55 °C 25 kvar at 400440 V AC 50/60 Hz 55 °C 36 kvar at 660690 V AC 50/60 Hz 55 °C
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	110 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 1 NC
Mounting support	Rail Plate
Standards	IEC 60831 VDE 0560 NF C 54-100 IEC 60070
Product certifications	UL CSA
Connections - terminals	Power circuit: connector 1 2.5 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 4 mm² - cable stiffness: solid with cable end Power circuit: connector 2 1.5 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 4 mm² - cable stiffness: solid with cable end
Tightening torque	Power circuit: 2.5 N.m - on connector

Complementary

Auxiliary contacts type type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1

Environment

IP degree of protection IP2x conforming to IEC 60529 IP2x conforming to VDE 0106

Feb 2, 2023 Life Is On Schneider

Protective treatment	TH conforming to IEC 60068-2-30
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-6080 °C
Operating altitude	3000 m without derating
Height	140 mm
Width	56 mm
Depth	122 mm
Net weight	0.63 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months

Recommended replacement(s)