## NSYPLM86P

wall-mounting encl. polyester monobloc IP66 H847xW636xD300mm+metal mount.plate



Main	
Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	33.35 in (847 mm)
Nominal width	25.04 in (636 mm)
Nominal depth	11.81 in (300 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 1 mounting plate 2 lock
Door type	Solid
Lock type	3 mm double-bar lock

_				
Ca	mp	lem	en:	tarv

1		
Number of locks	2	
Mounting plate description	Plain steel	
Accessibility for operation	Front	
Removable parts	Door by hinges Mounting plate by fixing element	
Material	Polyester reinforced with fibreglass	
Color	Gray RAL 7032)	
Standards	NEMA classification 13 IEC 62208 NEMA classification 4X	
Product Certifications	UL	

## Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 IEC 62262
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Storage	-31194 °F (-3590 °C)

## Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480192357
Returnability	No
Country of origin	ES

## Contractual warranty

Ochtractual warranty		
Warranty	18 months	