

## Hex bolts, Zinc plated grade 5 steel, 3/4"-10 x 4"

Bott Depot products Units US Category Hex bolts Botts with newagonal heads and machine threads for use with a nut or in a tapped hole. Also known as hex cap screws or machine boits.  Subcategory Hex bolts A bott with a six sided head.  Material Steel A low carbon steel for general use, either Grade 2 or A307A.  Plating Zinc plated for moderate corrosion resistance.  Grade Grade Sfalls between grade 2 and grade 8 in strength, and is commonly found in automotive applications.  Thread density Coerse  Diameter 3/4" Thread count 10 Length 4" Thread direction Right hand Length tolerance -0.08" / -0.10" Head style Hex Hex heads are six slided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height Uniter one of the six of	Product details	
Category         Hex bolts		446
Boits with hexagonal heads and machine threads for use with a nut or in a tapped hole. Also known as hex cap screws or machine boits.  Subcategory Hex boits A both with a six sided head.  Material Steel A low carbon steel for general use, either Grade 2 or A307A.  Plating Zinc Zinc plated for moderate corrosion resistance.  Grade Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive applications.  Thread density Coarse  Diameter 3/4"  Thread count 10  Length 4"  Thread direction Right hand  Length tolerance -0.08" / -0.10"  Head style Hex Hex hexagonal head for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Wridth across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1	Units	US
A bott with a six slided head.  Material Steel A low carbon steel for general use, either Grade 2 or A307A.  Plating Zinc Zinc plated for moderate corrosion resistance.  Grade Grade 5 Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive applications.  Thread density Coorse  Diameter 3/4"  Thread count 10  Length 4"  Thread direction Right hand  Length tolerance -0.08" / -0.10"  Head style Hex Hex heads are six slided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1	Category	Bolts with hexagonal heads and machine threads for use with a nut or in a tapped hole. Also known as
A low carbon steel for general use, either Grade 2 or A307A.  Plating Zinc Zinc plated for moderate corrosion resistance.  Grade Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive applications.  Thread density Coarse  Diameter 3/4"  Thread count 10  Length 4"  Thread direction Right hand  Length tolerance -0.08" / -0.10"  Head style Hex Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the fiats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  A SME B18.2.1	Subcategory	
Zinc plated for moderate corrosion resistance.  Grade Grade 5 Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive applications.  Thread density Coarse  Diameter 3/4°  Thread count 10  Length 4°  Thread direction Right hand  Length tolerance -0.08° / -0.10°  Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4°  Dimensional standard  A SME B18.2.1	Material	
Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive applications.  Thread density Coarse  Diameter 3/4"  Thread count 10  Length 4"  Thread direction Right hand  Length tolerance -0.08" / -0.10"  Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1	Plating	
Diameter 3/4"  Thread count 10  Length 4"  Thread direction Right hand  Length tolerance +0.08" / -0.10"  Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1	Grade	Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive
Thread count 10  Length 4"  Thread direction Right hand  Length tolerance +0.08" / -0.10"  Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1	Thread density	Coarse
Thread count 10  Length 4"  Thread direction Right hand  Length tolerance +0.08" / -0.10"  Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1		3/4"
Length 4°  Thread direction Right hand  Length tolerance +0.08° / -0.10°  Head style Hex Hex Hex Hex Hex Hex Hex Hex Hex He	Thread count	10
Length tolerance +0.08" / -0.10"  Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats 1-1/8"  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard ASME B18.2.1		4*
Head style Hex Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1		Right hand
Hex heads are six sided for use with a wrench.  Drive type External hex A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1		+0.08" / -0.10"
A hexagonal head for use with a wrench.  Head height 0.455" - 0.483"  Width across the flats 1-1/8"  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard ASME B18.2.1	Head style	
Width across the flats  Fully threaded No  Thread length Minimum 1-3/4"  Dimensional standard  ASME B18.2.1	Drive type	
Fully threaded No  Thread length Minimum 1-3/4"  DImensional standard ASME B18.2.1	Head height	0.455" - 0.483"
Thread length Minimum 1-3/4"  Dimensional standard ASME B18.2.1		1-1/8"
Thread length Minimum 1-3/4"  Dimensional standard ASME B18.2.1	-	No
standard		Minimum 1-3/4"
Material standard SAE J429		ASME B18.2.1
	Material standard	SAE J429