

Hex bolts, Zinc plated grade 5 steel, 1/2"-20 x 3"

| Product details | |
|-------------------------|---|
| | 520 |
| Bolt Depot product# | 529 |
| Units | US |
| Category | Hex bolts |
| | Boits with hexagonal heads and machine threads for use with a nut or in a tapped hole. Also known as hex cap screws or machine boits. |
| Subcategory | Hex bolts |
| | A boit with a six sided head. |
| Material | Steel |
| | A low carbon steel for general use, either Grade 2 or A307A. |
| Plating | Zinc |
| | Zinc plated for moderate corrosion resistance. |
| Grade | Grade 5 |
| | Grade 5 falls between grade 2 and grade 8 in strength, and is commonly found in automotive applications. |
| Thread density | Fine |
| Dlameter | 1/2" |
| Thread count | 20 |
| Length | 3" |
| Thread direction | Right hand |
| Length tolerance | +0.06" / -0.08" |
| Head style | Hex |
| | Hex heads are six sided for use with a wrench. |
| Drive type | External hex |
| | A hexagonal head for use with a wrench. |
| Head height | 0.302" - 0.323" |
| Width across the flats | 3/4" |
| Fully threaded | No |
| Thread length | Minimum 1-1/4" |
| Dimensional standard | ASME B18.2.1 |
| Material standard | SAE J429 |
| | |