

# Valor<sup>®</sup>2000 Compact Bench Scales

Model	V22PWE1501T V22XWE1501T	V22PWE3T V22XWE3T	V22PWE6T V22XWE6T	V22PWE15T V22XWE15T	V22PWE30T V22XWE30T
Capacity (max) x Readability (d)	1.5 kg × 0.0002 kg 1500 g × 0.2 g 3 lb × 0.0005 lb 48 oz × 0.01 oz 3 lb × 0.01 oz (lb:oz)	3 kg × 0.0005 kg 3000 g × 0.5 g 6 lb × 0.001 lb 96 oz × 0.02 oz 6 lb × 0.02 oz (lb:oz)	6 kg × 0.001 kg 6000 g × 1 g 15 lb × 0.002 lb 240 oz × 0.05 oz 15 lb × 0.05 oz (lb:oz)	15 kg × 0.002 kg 15000 g × 2 g 30 lb × 0.005 lb 480 oz × 0.1 oz 30 lb × 0.1 oz (lb:oz)	30 kg × 0.005 kg 30000 g × 5 g 60 lb × 0.01 lb 960 oz × 0.2 oz 60 lb × 0.2 oz (lb:oz)
Maximum Resolution (d)	1:7,500	1:6,000	1:6,000	1:7,500	1:6,000
Weighing Units	g, kg, lb, oz, lb:oz				
Application Modes	V22PW: Weighing V22XW: Weighing, Checkweighing				
Keyboard	V22PW: Two mechanical switches with polycarbonate overlay V22XW: Four mechanical switches with polycarbonate overlay				
Calibration	Digital external span calibration				
Display	7 segment, 6 digit, 20.5 mm / 0.8 in high red LED dual display				
Display Indicators	Stability, center of zero, net, battery status				
Tare Range	To capacity by subtraction				
Zero Range	-10% to 10% of Capacity				
Stabilization Time	≤0.5 second				
Safe Overload Capacity	150% of capacity				
Operation Temperature Range	-10 °C to 40 °C / 14° F to 104° F, 10% to 90% relative humidity non-condensing				
Construction	V22PW: stainless steel platform, ABS housing V22XW: Stainless steel top housing and platform, ABS bottom housing				
Power	12V DC 0.84A, AC Universal adapter (100 - 220V AC / 50 -60Hz) and built-in internal rechargeable lead acid battery included				
Battery Operation	Typically 50 hours of continuous use with 12-hour full charge				
Ingress Protection	IPX8 Washdown				
Pan Size	190 × 242 mm / 7.5 × 9.5 in				
Scale Dimensions (W × D × H)	V22PW: 256 × 280 × 121 mm / 10.1 × 11 × 4.8 in V22XW: 256 × 288 × 124 mm / 10.1 × 11.3 × 4.9 in				
Shipping Dimensions (W × D × H)	410 × 370 × 220mm / 16.1 × 14.6 × 8.7 in				
Net Weight	V22PW: 3.0 kg / 6.6 lb V22XW: 3.9 kg / 8.6 lb				
Shipping Weight	V22PW: 4.0 kg / 8.8 lb V22XW: 4.9 kg / 10.8 lb				

## Other Standard Features and Equipment

Level bubble, easy-to-transport carrying handle, removable stainless steel platform and chemical-resistant overlay, mechanical keys, spring loaded cover to protect power connector of scale

## Compliance

- **Product Safety:** IEC 61010-1; CAN/CSA C22.2 No. 61010-1; UL Std. No. 61010-1
- **Electromagnetic Compatibility:** FCC Part 15; Industry Canada ICES-003 – Class B ; IEC 61326-1 - Class B, Basic environments
- **Ingress Protection:** IEC 60529 – IPX8
- **Food Safety:** NSF/ANSI 169; NSF/ANSI /3-A 14159-1
- **Other:** RoHS

## Accessory

Stainless Steel Platform, 300 x 225 mm . . . . .30251753

## OHAUS CORPORATION

\* 7 Campus Drive  
Suite 310  
Parsippany, NJ 07054 USA

Tel: 800.672.7722  
973.377.9000  
Fax: 973.944.7177

[www.ohaus.com](http://www.ohaus.com)

With offices throughout  
Europe, Asia, and  
Latin America

## \*ISO 9001:2008

Registered Quality  
Management System

