


WEPDMC Cold Shrink EPDM Tube



- Manufactured from EPDM rubber.
- Offering good mechanical, insulation and sealing protection.
- Accommodating a wide range of cable sizes.
- For indoor or outdoor applications.
- Simple and fast installation.

Selection Table

Cold Shrink Tube of General EPDM					
Product No.	Size	Application Range (mm/inch)	Length after Relaxed(mm/inch)	Material	Color
8320-L	Φ20	8~15/0.30~0.59	50~550/2~22	EPDM Rubber	Black
8325-L	Φ25	10~20/0.39~0.79	50~550/2~22	EPDM Rubber	Black
8335-L	Φ35	14~30/0.55~1.18	50~550/2~22	EPDM Rubber	Black
8340-L	Φ40	17.5~33/0.69~1.30	50~550/2~22	EPDM Rubber	Black
8353-L	Φ53	25~46/0.98~1.81	50~550/2~22	EPDM Rubber	Black
8370-L	Φ70	32~63/1.26~2.48	50~470/2~18	EPDM Rubber	Black
8104-L	Φ104	43~94/1.69~3.70	50~470/2~18	EPDM Rubber	Black
8125-L	Φ125	46~114/1.81~4.49	50~470/2~18	EPDM Rubber	Black
8150-L	Φ150	55~135/2.17~5.31	50~470/2~18	EPDM Rubber	Black

Cold Shrink Tube of High Shrinkage Ratio EPDM					
Product No.	Size	Application Range (mm/inch)	Length after Relaxed(mm/inch)	Material	Color
8435-L	Φ35	12.5~30/0.49~1.18	50~550/2~22	EPDM Rubber	Black
8440-L	Φ40	14~33/0.55~1.30	50~550/2~22	EPDM Rubber	Black
8453-L	Φ53	19~46/0.75~1.81	50~550/2~22	EPDM Rubber	Black
8470-L	Φ70	25~63/0.98~2.48	50~470/2~18	EPDM Rubber	Black
8480-L	Φ80	27.4~70/1.08~2.75	50~470/2~18	EPDM Rubber	Black

Remark: L indicates the required length after relaxed with the unit of mm or inch.