

Product data sheet

Specifications



1 tone siren - 106 dB - 24 V AC DC

XVSB1

! Discontinued on: 22 January 2021

! Discontinued

Main

Range of product	Harmony XVS Application
Product or component type	Siren
Device short name	XVS
Signalling type	1 tone siren
[Us] rated supply voltage	24 V AC/DC
Noise level	106 dB
Cable end type	With cable end

Complementary

Material	Butadiene styrene acrylic: cone Glass reinforced polyamide 6: body
Net weight	0.86 kg
Operating position	Any position
[Ui] rated insulation voltage	250 V conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	1.5 kV conforming to EN/IEC 60947-1
Current consumption	440 mA
Sound frequency	1000 Hz +/- 10 %
Clamping connection capacity	<= 1 x 1.5 mm ²
Cable entry	1 tapped entry for cable gland (included) for Pg 7

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-40...50 °C
Electrical shock protection class	Class III conforming to EN/IEC 61140

IP degree of protection IP40

Contractual warranty

Warranty 18 months

Recommended replacement(s)